

System	RHP75 ( Head ) + RT50C ( Tripod ) + SP-2B ( Floor spreader ) + RC-70 ( Carrying case )		
Payload	17 kg / 37.5 lb	Tilt angle	+90° / -70° ( Limited to ±40° with maximum counterbalance )
Weight	7.5 kg / 16.5 lb	Pan angle	360°
Height	① H: 1755 mm W: 710 mm (※Reference)	Counterbalance	Range : 5.5~14 kg / 12~31 lb (CG125mm)
	② H: 650 mm W: 1100 mm ( " )		System : Continuous
Folded length	③ L: 915 mm ( " )	Drag mode	7 STEP
Camera plate (Sliding range)	Sliding plate ±55 mm / 2.2"	Ball diameter	∅100 mm
Plate attachment (Screw sliding range)	Type : 3/8-16UNC × 2	Section	2STAGE (Material: Aluminum)
	102 mm / ±4"	Tripod fixation	Fixing lock knob
Spare screw	Type : 3/8-16UNC × 1	Spreader	SP-2B (Telescopic, Removable)
	Equipped on the head ( Behind the platform of sliding plate )	Pan handle	PH-8B
		Case material	Nylon , Polyester , TPE , PE , PP

### Remarks

### ■ Exterior Dimensions (mm)

#### ■ RHP75

